



Hvem smører egentligt din HSK-spindel?

Lubritool® smører din spindel automatisk på bare 5 sekunder



Fås nu også til HSK-A40
og HSK-A50

LUBRITOOL® SMØREVÆRKTØJ

- ➔ Hurtigt + automatisk: smøring på 5 sekunder
- ➔ Øger maskinens effektivitet med 10 timer/pr. år
- ➔ Præcis dosering for optimal smøring

LUBRITool® LUBRICATION DEVICE

In order to guarantee the impeccable functioning of milling machines and machining centres, the tool clamping system should be maintained regularly. The patent-pending Lubritool® lubrication device enables automatic lubrication within 5 seconds.

Traditionally, manual lubrication consisted of a maintenance effort of several minutes. RÖHM developed its Lubritool® lubrication device to make these routine downtimes a thing of the past. When the CNC control senses the need

for lubrication, it sends a command and the Lubritool® is automatically deployed directly from the tool magazine to supply the tool clamping system with the ideal quantity of lubricant within seconds.

HOW LUBRITool® WORKS IN YOUR MACHINE TOOL



Lubritool® is located in the tool magazine. Whenever the machine control notifies that a lubrication process is necessary, Lubritool® will be sent up into the spindle.



The lubrication impulse is automatically activated within the spindle. An optimal quantity of Lubriflux lubricant is sprayed onto the right place of the tool clamping system.



After the lubrication process, Lubritool® is sent back to the tool magazine and remains there until the next lubrication cycle.

This is how Lubritool® works:
Video on its use



WHY LUBRITOOL®?



1

OPTIMAL LUBRICATION:

The ideal lubricant. Just at the right time.
In the right quantity and place.

2

MINIMAL MAINTENANCE TIMES:

Lubrication in 5 seconds rather than 5 minutes.
Increasing the machine availability by about 10 hours/year.

3

AUTOMATED LUBRICATION:

Never forget the maintenance again.
Increase the service life of the clamping sets.

4


COMPACT DESIGN:

Fits in any conventional machine tool.

5

RESOURCE-EFFICIENT LUBRICATION:

Precision dosing of the lubricant.



Fås nu også til HSK-A40
og HSK-A50

Lubritool® lubrication device	ID 1334394 NEW	D 1334306 NEW	ID 1330233	ID 1323415
Price Lubritool®	6195 DKK	6195 DKK	6195 DKK	6818 DKK
Interface design (ISO12164-1)	HSK-A40	HSK-A50	HSK-A63	HSK-A100
a mm	51	52	54	57
b mm	194.5	195.5	197.5	200.5
Ø c mm	65	65	65	65
Weight kg (without cartridge)	1.0	1.1	1.4	2.7
Weight kg (with cartridge)	1.2	1.3	1.6	2.9
Lubrication applications	100 cycles	100 cycles	100 cycles	100 cycles
Lubrifix grease cartridge (1 piece)	ID 1339629	ID 1339629	ID 1339629	ID 1339629
Price Lubrifix	1071 DKK	1071 DKK	1071 DKK	1071 DKK

Other sizes "CAPTO C6" and "KM 4X63" are in preparation.
Lubritool® is approved for all clamping sets from RÖHM and OTT Jakob.

RÖHM Worldwide



With more than 50 subsidiaries and representatives, RÖHM is present on all continents and is very close to the customer everywhere.

Find your personal contact person:
www.roehm.biz



O. RYTTERGAARD VÆRKTØJ A/S
FALKEVEJ 13, 3400 HILLERØD, TLF.: 36 70 65 55
INFO@RYTTERGAARD.COM - WWW.RYTTERGAARD.COM